



P2028 Alphanumeric Pocket Pager - 2 Line / 4 Line Pager

The P2028 is a modern VHF/UHF POCSAG alphanumeric pager. The pager comes with 8 paging addresses and is feature rich. The pager is synthesized in the appropriate band. The pager can be viewed in 2 or 4 lines. The pager battery life can typically achieve 2000 hours in 512 bps with an alkaline battery. Modern, ergonomic, light weight design and easy to use.

Features

- Simple and easy to use
- 1 Year Warranty
- Hand Programmable
- Lock Down feature in programming software
- Selectable alerts – silent, vibrate, various tones and music
- Out of range indicator
- Duplicate message rejection if required
- Low battery warning
- Unread reminder message
- Time, date and alarms message time stamps

Specifications

- Frequencies :
 - VHF 138-143, 143-151, 151-159, 159-167, 167-174MHz.
 - UHF 448-452, 452-256, 456-460, 460-464, 464-468, 468-472 MHz.
- Signal Format : POCSAG 512 or 1200
- Capcodes : 8
- Message Capacity : 19 Messages up to 512 characters each
- LCD Display : 4 lines x 20 characters or zoom to 2 line x 20 characters
- LCD Backlight : White LED
- Channel Spacing : 25KHz wide band (+_4.5KHz deviation)
- RX Sensitivity : 512bps 5uV/m, 1200bps 7uV/m
- Battery : 1x AAA Alkaline
- Dimensions : 80Lx54Wx19H mm
- Weight : 135g with battery
- Battery Life : up to 80 days using alkaline battery
- Approvals : CE, FCC, RCM, RoHS

System Solutions

- In House Paging
- Nursing Homes
- Hospitals
- Rehabilitation Hospitals
- Nurse Call Systems
- Fire Interface Panels
- Highrise Building Alerts
- Security Systems
- Police Stations
- Government Facilities
- Defence Grounds and Buildings
- Council Building/Grounds
- Remote Alarm Activation/Acknowledgement (Option)

Description [Part Numbers]

P2028 VHF Pager	[50-1501]
P2028 UHF Pager	[50-2501]

Please contact PACTechnika for more information

